

MVL-MF0828M-8MP

2/3" 8mm 8MP FA Lens


MF series FA Lens are optimized for machine vision light sources and sensor, with high resolution, excellent image quality, high transmittance and good stability. Featured with fixed focal length, manual aperture and compact size, it is suitable for machine vision industry applications and ideal for industrial cameras.




Key Features

- Ultra-high resolution and consistency of image clarity
- Ultra-low distortion and higher relative illumination
- Achromatic optical system design, better image performance with color camera
- Supports ultra-short working distance with good optical performance
- Compact design, excellent vibration resistance and high and low temperature performance


Distortion



MTF



Relative Illumination




Note: The above curves are the simulate results based on F2.8, $\beta = -0.03$, WD=250 mm.



Specification

Parameter	Model	MVL-MF0828-8MP
	Fixed focal length, Manual iris, 8MP, FA Lens	
Performance		
Focal Length	8 mm	
F-Number	F2.8 ~ F16	
Image Size	Φ11 mm(2/3″)	
Distortion	0.28%	
Minimum Operation Distance	0.1 m	
Field of View	D (11.1 mm) : 68.46° H (8.45 mm) : 54.97° V (7.07 mm) : 47.06°	
Mechanical		
Iris Control	Manual	
Focus Control	Manual	
Mount	C-Mount	
Flange Back Length	17.526 mm	
Dimension	Φ35×40.27 mm	
Weight	80.7 g	
Temperature	-10 ~ 50℃	
General		
Certification	RoHS2.0	

Dimension



Unit: mm

Field of View

Extension (mm)	Working Distance (mm)		Magnification	Field of View (mm)					
				2/3"		1/1.8"		1/2"	
				H(8.45mm)	V(7.07mm)	H(7.38mm)	V(4.92mm)	H(6.22mm)	V(4.67mm)
2	near	8.86	-0.319	26.49	22.16	23.13	15.42	19.50	14.64
	far	15.46	-0.250	33.79	28.27	29.51	19.67	24.87	18.67
1	near	25.02	-0.194	43.56	36.44	38.04	25.36	32.06	24.07
	far	47.43	-0.125	67.56	56.52	59.00	39.33	49.73	37.34
0	100		-0.069	125.75	104.62	109.35	72.25	91.75	68.52
	150		-0.049	183.02	151.33	159.26	105.19	133.67	99.74
	200		-0.037	230.95	192.65	201.25	133.40	169.16	126.55
	250		-0.030	282.15	235.78	246.01	163.27	206.91	154.91
	300		-0.025	334.04	279.34	291.36	193.49	245.13	183.59
	350		-0.022	395.07	328.41	344.53	228.43	289.73	216.66
	400		-0.019	437.82	366.46	382.07	253.93	321.57	240.96
	450		-0.017	489.71	410.03	427.42	284.16	359.80	269.64
	500		-0.016	545.97	456.36	476.48	316.62	401.04	300.41
	550		-0.014	598.28	500.19	522.19	347.05	439.55	329.30
	600		-0.013	650.58	544.01	567.90	377.49	478.06	358.18
	650		-0.012	702.89	587.84	613.60	407.92	516.57	387.07
	700		-0.011	756.08	632.22	660.06	438.82	555.69	416.38
	800		-0.010	860.81	719.95	751.58	499.75	632.80	474.20
	900		-0.009	965.54	807.68	843.09	560.59	709.91	532.03
	1000		-0.008	1070.95	895.82	935.18	621.97	787.48	590.18

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.
en.hikrobotics.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.