

# MV-CA032-10GM/GC

3.2 MP 1/1.8" CMOS GigE Area Scan Camera

GEN*i*CAM

GIG*E* VISION



## Introduction

MV-CA032-10GM/GC camera adopts Sony IMX265 sensor to provide high-quality image. It uses GigE interface to transmit non-compressed images in real time with max. frame rate reaching 37.5 fps.

## Key Feature

- Adopts GigE interface and max. transmission distance of 100 meters without relay
- Supports auto and manual adjustment for exposure control, LUT, Gamma correction, etc.
- Up to 128 MB local memory for burst transmission and retransmission
- Supports hardware trigger, software trigger, etc.
- Compatible with GigE Vision Protocol V2.0, GenICam Standard, and third-party software based on these protocol and standard


## Available Model

Mono camera: MV-CA032-10GM  
Color camera: MV-CA032-10GC


## Applicable Industry

Electronic semiconductor, factory automation, food and beverage, medical packaging, etc.

## Sensor Quantum Efficiency




MV-CA032-10GM



MV-CA032-10GC

## Dimension



Unit : mm



## Specification

Model	MV-CA032-10GM	MV-CA032-10GC
<b>Camera</b>		
Sensor type	CMOS, global shutter	
Sensor model	Sony IMX265	
Pixel size	3.45 $\mu\text{m}$ x 3.45 $\mu\text{m}$	
Sensor size	1/1.8"	
Resolution	2048 x 1536	
Max. frame rate	37.5 fps @2048 x 1536	
Dynamic range	73 dB	
SNR	40 dB	
Gain	0 dB to 20 dB	
Exposure time	UltraShort exposure mode: 1 $\mu\text{s}$ to 14 $\mu\text{s}$	
	Standard exposure mode: 15 $\mu\text{s}$ to 10 s	
Shutter mode	Off/Once/Continuous exposure mode	
Mono/color	Mono	Color
Pixel format	Mono 8/10/10p/12/12p	Mono 8/10/12, Bayer RG 8/10/10p/12/12p, YUV422Packed, YUV422_YUYV_Packed, RGB 8, BGR 8
Binning	Supports 1 x 2, 1 x 4, 2 x 1, 2 x 2, 2 x 4, 4 x 1, 4 x 2, 4 x 4	
Decimation	Supports 1 x 2, 2 x 1, 2 x 2	
Reverse image	Supports horizontal and vertical reverse image output	
Image buffer	128 MB	
<b>Electrical features</b>		
Data interface	Gigabit Ethernet	
Digital I/O	6-pin Hirose connector provides power and I/O, including opto-isolated input x 1 (Line0), opto-isolated output x 1 (Line1), and bi-directional non-isolated I/O x 1 (Line2)	
Power supply	5 VDC to 15 VDC, supports PoE power supply	
Power consumption	< 3.2 W@12 VDC	< 3.5 W@12 VDC
<b>Structure</b>		
Lens mount	C-Mount	
Dimension	29 mm x 29 mm x 42 mm (1.1" x 1.1" x 1.7")	
Weight	Approx. 68 g (0.15 lb.)	
Ingress protection	IP30 (under proper lens installation and wiring)	
Temperature	Working temperature: 0 $^{\circ}\text{C}$ to 50 $^{\circ}\text{C}$ (32 $^{\circ}\text{F}$ to 122 $^{\circ}\text{F}$ )	
	Storage temperature: -30 $^{\circ}\text{C}$ to 70 $^{\circ}\text{C}$ (-22 $^{\circ}\text{F}$ to 158 $^{\circ}\text{F}$ )	
Humidity	20% to 80% RH, without condensation	
<b>General</b>		
Client software	MVS or third-party software meeting with GigE Vision Protocol	
Operation system	32/64-bit Windows XP/7/10, 32/64-bit Linux and 64-bit MacOS	
Compatibility	GigE Vision V2.0, GenICam	
Certifications	CE, FCC, RoHS, KC	

### HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.  
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.  
en.hikrobotics.com

### MaxxVision®

Sigmaringer Str. 121  
70567 Stuttgart  
Tel.: 0711 997 996 3  
www.maxxvision.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.