

MV-CE050-30GM

5 MP 1/2.5" CMOS GigE Area Scan Camera



GEN*i*CAM

GIG*E* VISION


Introduction

MV-CE050-30GM camera is a high quality device that can be used in a variety of applications, including electronic semiconductor fabrication, factory automation, quality inspection.

Key Feature

- Adopts GigE interface and max. transmission distance of 100 meters without relay
- Up to 128 MB local memory for burst transmission and retransmission
- Supports auto exposure control, LUT, Gamma correction, etc.
- Supports hardware trigger, software trigger, etc.
- Compatible with GigE Vision V1.2 Protocol, GenICam Standard, and third-party software based on the protocol and standard

Dimension




Available Model

Mono camera: MV-CE050-30GM

Applicable Industry

Electronic semiconductor, factory automation, quality inspection.

Sensor Quantum Efficiency



Specification

Model	MV-CE050-30GM
Camera	
Sensor type	COMS, rolling shutter
Sensor model	MT9P031
Pixel size	2.2 μm $\times$ 2.2 μm
Sensor size	1/2.5"
Resolution	2592 $\times$ 1944
Max. frame rate	14 fps @2592 $\times$ 1944
Dynamic range	60 dB
SNR	38 dB
Gain	0 dB to 20 dB
Exposure time	34 μs to 1 s
Shutter mode	Off/Once/Continuous exposure mode
Mono/color	Mono
Pixel format	Mono 8/10/10p/12/12p
Binning	Not support
Decimation	Not support
Image buffer	128 MB
Electrical features	
Data interface	Gigabit Ethernet
Digital I/O	Opto-isolated input $\times$ 1, Opto-isolated output $\times$ 1, Bi-directional non-isolated I/O $\times$ 1
Power supply	Voltage range: 5 VDC to 15 VDC, supports PoE power supply
Power consumption	< 2.75 W@12 VDC
Structure	
Lens mount	C-Mount
Dimension	29 mm $\times$ 29 mm $\times$ 42 mm (1.1" $\times$ 1.1" $\times$ 1.7")
Weight	Approx. 68 g (0.15 lb.)
Ingress protection	IP30 (under proper lens installation and wiring)
Temperature	Working temperature: 0 $^{\circ}\text{C}$ to 50 $^{\circ}\text{C}$ (32 $^{\circ}\text{F}$ to 122 $^{\circ}\text{F}$) Storage temperature: -30 $^{\circ}\text{C}$ to 70 $^{\circ}\text{C}$ (-22 $^{\circ}\text{F}$ to 158 $^{\circ}\text{F}$)
Humidity	20% to 80% RH, without condensation
General	
Client software	MVS or Third-Party Software meeting with GigE Vision Protocol
Operating system	32/64-bit Windows XP/7/10, 32/64-bit Linux and 64-bit MacOS
Compatibility	GigE Vision
Certification	CE, FCC, RoHS, KC

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.
en.hikrobotics.com

MaxxVision®

Sigmaringer Str. 121
70567 Stuttgart
Tel.: 0711 997 996 3
www.maxxvision.com