

MV-SI638-08GM/GC

6.0 MP X86 Open Platform



Introduction

MV-SI638-08GM/GC is an open platform for users to develop their own programs according to actual demands. It has multiple interfaces, such as IO, serial port and extended interface, to communicate with other devices.

Key Feature

- Adopts sensor platform for high-speed image processing.
- Open platform for users to develop their own programs.
- Multiple IO interfaces for input and output signals.
- Multiple LED indicators indicating real-time status to assist the configuration and debugging on site.
- Supports saving and exporting logs.
- Supports external extended module for meeting different application demands.


Available Model

- Mono X86 open platform: MV-SI638-08GM
- Color X86 open platform: MV-SI638-08GC

Applicable Industry

Consumer electronics, food and beverage, pharmaceutical, automobile, etc.

Dimension



Unit: mm



Specification

Model	MV-SI638-08GM	MV-SI638-08GC
Tools		
Function module	Open platform	
Camera		
Sensor type	CMOS, rolling shutter	
Sensor model	Sony® IMX178	
Pixel size	2.4 μm × 2.4 μm	
Sensor size	1/1.8"	
Resolution	3072 × 2048	
Max. frame rate	17 fps	
Dynamic range	71.3 dB	
SNR	41.3 dB	
Gain	0 dB to 15 dB	
Exposure time	27 μs to 2.5 s	
Pixel format	Mono 8	Mono 8, Bayer GB 8, RGB 8
Mono/color	Mono	Color
Platform		
System framework	Intel® X86 framework. Intel® E3845, quad-core CPU, 1.9 GHz	
Memory	DDR3L 4 GB	
Storage	128 GB SSD	
Electrical features		
Data interface	Gigabit Ethernet interface	
Digital IO	12-pin M12 connector, including opto input × 3 (LineIn 0/1/2), opto output × 3 (LineOut 0/1/2), and RS-232 × 1.	
Extended interface	17-pin extended interface for connecting extended module	
Power supply	9 VDC to 24 VDC	
Power consumption	Approx. 34 W@24 VDC	
Structure		
Lens mount	C-mount	
Lens cap	Transparent lens cap	
Lighting	White light	
Indicator	Power indicator (PWR), network indicator (LNK/ACT), and user-defined indicator (U1/U2)	
Dimension	126 mm × 66 mm × 113.2 mm (5.0" × 2.6" × 4.5")	
Weight	Approx. 750 g (1.7 lb.)	
Ingress protection	IP67 (under proper installation of lens and wiring)	
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -30 °C to 70 °C (-22 °F to 158 °F)	
Humidity	20% to 95% RH, non-condensing	
General		
Operating method	MVS	
Operating system	64-bit Windows 10	
Certifications	CE, FCC, RoHS	

HIKROBOT

Hangzhou Hikrobot Technology Co., Ltd.
No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.
en.hikrobotics.com

MaxxVision®

Sigmaringer Str. 121
70567 Stuttgart
Tel.: 0711 997 996 3
www.maxxvision.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any org content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and oper the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsisten