

Dual Camera Full 4K Encoder

Designed for your Visible & IR Monitoring Needs **FV4K-13A**

- H.265/H.264 Dual Camera Video Streaming
- Interfaces with HDMI, LVDS, and Composite cameras
- High Quality Low Latency Encoding
- Pass Camera Control Commands over IP
- ONVIF Profile S and T Compliant

The FV4K-13A is designed for dual camera inspection surveillance, industrial or UAV applications. The encoder supports both H.265 and H.264 encoding for visible and thermal cameras. The dual camera encoding allows for a 4K HDMI camera and a second LVDS or Composite Camera to be streamed from the encoder. The encoder can simultaneously stream and record video to either a Network File System, USB or Micro SD card. Controls are through the web user interface, Serial/SSH, the API or ONVIF. Additional processing is supported within the system to allow for Overlays on the video or data to be sent in the data stream.





Technical

Interfaces	
•Visible Camera Formats	Sony FCB-EV-/EW-/ER-Series, Tamron MP-Series, Micro HDMI
•HD and SD IR Formats	RS170, NTSC/PAL and LVDS
• Recording	To either USB, Micro SD or NFS
 Additional Interfaces 	GbE, Audio Input, RS-232, Micro-HDMI Passthrough, POE, Composite Output, Serial I/O (RS-232, RS-422, RS-485)
Video Codecs	H.265 & H.264
Encoding Resolutions	4Kp30, 1080p (up to 60fps), 720p, NTSC/PAL, VGA, CIF and QVGA
Output Formats	RTP, RTSP, MPEG-2 TS and RTMP ¹
Features	 Easy-to-Use HTTP/HTTPS web GUI with live video preview Pass VISCA™ Camera Control Commands over IP ONVIF® Profile S and T Simultaneous Stream and Record Overlay of GPS or NTP Data SRT Modes Supported: Caller, Sender, Rendezvous & SRT Encryption Pelco D PTZ Positioning Absolute PTZ Support Compatible with ZEUS® DMD-4K Video Decoder Timestamp and KLV support through overlay or SEI data

ORDERING OPTIONS

FV4K-13A

OEM Production Set

FV4K-13A-1x Encoder Boards

Note: Sony FCB-ER Series Camera Blocks and KEL ribbon cable sold separately*

FV4K-13A-RPS **OEM Starter Kit**

- FV4K-13A Encoder Boards
- Power Supply
- · Software SDK
- Documentation
- · Serial Cable
- (2) KEL Cables

Note: Sony FCB-ER Series Camera Block sold separately

APPLICATIONS

Inspection Security and Surveillance Industrial **UAV** and Drones


Customized Applications*


Specifications \

-	
Encoder Board Size	75 x 50 x 33 mm (2.95 x 1.97 x 1.30 in)
Encoder Board Weight	85g
Power Consumption	4.5W
Power Supply	12V DC or PoE 802.3af/at class 0



FV4K-13A Encoder





Z³ Technology is an industry-leading, USA-based manufacturer of production-ready embedded multimedia solutions and IP camera systems. From our founders to our world-class engineers to our sales and customer service team, we understand your requirements and speak your language. Our experience allows us to provide cost-effective solutions to meet your multimedia product requirements. With the assistance of our robust worldwide distribution and sales networks, we can provide a simple solution for your multimedia needs.

